



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*0033*03

Reason for extension: Increase of S-value from 100 kg to 120 kg.

SECTION I

0.1. Make (trade name of manufacturer) : Bosal

0.2. Type and general commercial description(s) : 901 2098

0.3. Means of identification of type marked on the : Type approval number

component

0.5.

0.3.1. Location of that marking : On type plate

Postbus 168

4920 AD Made

0.7. In the case of components and separate technical: On type plate

affixing of the EEC type approval mark

units, location and method of

Name and address of manufacturer

0.8. Address(es) of assembly plant(s) : See information document

(annex III, item 0.8)

Bosal

Type-approval number: e4*94/20*0033*03

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76 8218 NX Lelystad

3. Date of test report

01-03-1995

05-08-1998

4. Number of test report

TC-68-94/20-028/95 TCL-94/20-843/97

5. Remarks (if any)

: See Appendix I

6. Place

: Zoetermeer

7. Date

: 15-07-2003

8. Signature

J.P.M. Laumen

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I to EEC type-approval certificate I

to EEC type-approval certificate No: e4*94/20*0033*03 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1	A dditional	information
4 .	Addinonal	miormanon

1.1. Class of the type of coupling

A50-X

1.2. Categories or types of vehicles for which

the device is designed or restricted

: See fitting instructions

1.3. Maximum D-value

1.6.

15,26

kN

1.4. Maximum vertical load S at the coupling point:

100 120

kg kg

1.5 Maximum load U at the fifth wheel

ton

coupling point

6. Maximum V-value

kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or

type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles : See fitting instructions



1.8 Information on the fitting of special towing

brackets or mounting plates

: See fitting instructions

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.