



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO ATF CVT

VAICO No.:

V60-0117, V60-0211, V60-0212, V60-0213

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Extremely high viscosity index
- Excellent wear protection for longest life
- Excellent metal / metal frictional behavior for quiet switching without vibration and outstanding torque transmission
- Unrivalled viscosity-temperature behavior
- Outstanding oxidation and ageing stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Suitable for continuously variable transmission with steel-steel thrust belts or chains.
- Do not mix with other transmission fluids.
- Not suitable for use in hybrid CVT's (Honda/Ford), DCT/DSG
- (Dual clutch transmissions) or automatic stages.
- Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Fit to*:

Audi/VW TL 521 80, G 052 180 A2, TL 52 516, G 052 516 A2

BMW EZL799/-A, 83 22 0 136 376, 83 22 0 429 154

Chrysler/Dodge/Jeep NS-II, CVTF+4

Ford WSS-M2C928-A, CVT23, CVT30, GM DEX-CVT

Honda HMMF, HCF2, ATF-Z1

Hyundai/Kia A SP-III

Mazda JWS 3320

MB 236.20, 001 989 46 03

Mitsubishi CVTF-J1/-J4/-J4+, NS-II, SP-III

Nissan NS-I/-II/-III

Suzuki TC, NS-II, CVT Green 1/-1V/-2

Subaru NS-II, CVTF/-II

Toyota CVTF TC/-FE



PRODUCT DATA



TYPICAL VALUES	METHOD	UNIT	VAICO ATF CVT
Density at 15°C	DIN 51 757	g/cm ³	0,845
Viscosity at 40°C	DIN ISO 3104	mm ² /s	36
Viscosity at 100°C	DIN ISO 3104	mm ² /s	7,3
Viscosity index (VI)	DIN ISO 2909	-	173
Viscosity at -40°C	DIN 51 938	mPa.s	11.900
COC flash point	DIN ISO 2592	°C	210
Pour point	DIN ISO 3016	°C	- 51

*conforms to OEM specifications – The above values may vary within commercially accepted tolerances