



DEXRON IID

Automatic gearbox lubricant

Power steering system

Torque converters and hydraulic systems

TYPE OF USE

Automatic Transmission Fluid (ATF) for all systems where DEXRON II standard is required

Automatic gearboxes and transmissions, torque converters, power steering systems, hydraulic circuits, boat reversing gears...

PERFORMANCES

APPROVALS	MAN 339 Typ Z1 and V1 – MB-Approval 236.7 – VOITH 55.6335.32 (G607) ZF TE ML-03D / 04D / 11A / 14A / 17C
PERFORMANCE	GENERAL MOTORS DEXRON II D ALLISON C-4 – CATERPILLAR TO-2

Very high fluidity at low temperatures which allows easy gear changing.
Thermal stability under high temperature.
Anti-wear, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

MOTUL DEXRON II D is the latest evolution from DEXRON specification.
Can be used each time "DEXRON B" specification is recommended.
Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.865
Viscosity at 40°C (104°F)	ASTM D445	38.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.8 mm ² /s
Viscosity index	ASTM D2270	179
Flash point	ASTM D92	224°C / 435°F
Pour point	ASTM D97	< -36°C / < -33°F