

VCA Headquarters I The Eastgate Office Centre Eastgate Road Bristol, BS5 6XX United Kingdom

 Switchboard:
 +44 (0) 117 951 5151

 Direct line:
 +44 (0) 117 952<sup>4171</sup>

 Main Fax:
 +44 (0) 117 952 4103

 Email:
 enquiries@vc.agov.uk

 Web:
 www.vca.gov.uk

### THE UNITED KINGDOM VEHICLE APPROVAL AUTHORITY

Rev 1/03



COMMUNICATION CONCERNING THE APPROVAL GRANTED OF A REPLACEMENT BRAKE LINING ASSEMBLY OR REPLACEMENT DRUM LINING PURSUANT TO ECE REGULATION NO: 90.01

Approval No: 90R-01184 / 4197

1. Applicant's name and address:

Juratek Ltd. Unit 16, Carcroft Enterprise Park, Station Road, Doncaster DN6 8DD

- 2. Manufacturer's name and address:
- 3. Make and type of brake lining assembly: L0381.
- 4. Make and type of brake lining: LE TD3 GG
- 5. Vehicles/axles/brakes for which the brake lining assembly/drum brake lining type qualifies as original brake lining assembly: Not applicable
- 6. Vehicles for which the brake lining assembly qualifies as replacement brake lining assembly: See manufacturers Documents :-

An executive agency of the Department for Transport



- 7. Submitted for approval on: 1 August 2007
- 8. Technical Service responsible for approval tests: Vehicle Certification Agency
- 8.1 Date of test report: 14/08/06, 20/11/06, 15/08/06.
- 8.2 Number of test report: VSG076369, VSG078081, VSG078079.
- 9. Approval: GRANTED
- 10. Place: BRISTOL
- 11. Date: 19 SEPTEMBER 2007

Stenn Signature: 12.

A. W. STENNING Head of Product Certification

13. Annexed to this communication is a list of documents in the approval file deposited at the administrative services having delivered the approval and which can be obtained upon request.

VSH180956



01/08/07 VCA JOB NO VSH180956	01/08/07	VCA Job No	VSH180956
-------------------------------	----------	------------	-----------

Dear Claire,

Please find enclosed the necessary documentation for you to submit applications for approval for various brake lining assemblies L0381 in LE TD3 GG material pursuant to ECE Regulation No. 90/1. This application is on behalf of Juratek Ltd and cross-references to our L0 LE TD3 GG application details. We would like the application made to the VCA; I have addressed the formal letter of application accordingly.

The documents contained are: -

- 1. Formal letter of application
- 2. Manufacturers declarations
- 3. Lab test results :-
  - Friction test results
  - Shear test results
  - Compressibility test results
- 4. Vehicle fitment details
- 5. Disc pad assembly drawings
- 6. General disc pad marking drawing

Please note: Allocated with E11 90R-01184/4197 as a provisional number. This approval is based on VSG076369, VSG078081, and VSG078079 plus additional OE Materials testing on VSG076364 and VSG078099

Yours sincerely,

Susan Owens Q.B.T.



a 1 / a a / a =		
01/08/07	VCA Job No	VSH180956

Vehicle Certification Agency 1 Eastgate Office Centre Eastgate Road Bristol BS5 6XX

#### Letter of application for an approval pursuant to ECE Regulation No. 90/1

Dear Sirs,

Herewith we apply for an approval for our brake lining assembly pursuant to ECE Regulation No. 90/1.

Applicants name and address:

Juratek Ltd. Unit 16, Carcroft Enterprise Park, Station Road, Doncaster DN6 8DD

Manufacturers name and address:

Make and type of brake lining

LE TD3 GG

Make and type of brake lining assembly as listed below

Assembly Number	Assembly Contains(see enclosed drawings)	Material Code
L0381	4 identical pads with 2 wear indicators supplied loose	LE TD3 GG



01/08/07	VCA Job No	VSH180956
----------	------------	-----------

For vehicles / axles / brakes for which the lining assembly qualifies as replacement brake lining assembly, see following application list.

Assembly Number	Equivalent to	Also supplied as Assembly Number
	Equivalent to	
L0381 LE TD3 GG	Equivalent to	
	Equivalent to	
	Equivalent to	

Yours faithfully

vens wan

Susan Owens Q.B.T.



01/08/07	VCA Job No	VSH180956	
Manufacturer's Declaration			
for granting of	Approval for replace ECE Regulation No	ement brake lining according to . 90/1.	
We, the company			
declare herewith that			
Replacement pad assemblies	L0381 LE TD3 G0	3	
are produced in our factory			

We certify that no application has been made regarding this permission/approval by us or by companies appointed by us in countries which as contract parties would also be entitled to grant permission/approval.

We are aware of the following: -

A type marking of vehicles/vehicle components of the above mentioned type with the officially assigned approval mark can only be granted if the products have been manufactured in the above mentioned factory or at one of our listed and approved manufacturing sites, and if they comply with the official approval documents.

Companies manufacturing products for our company or under license may not use the officially assigned approval mark for vehicles/vehicle components produced at their factories unless they are listed as an approved manufacturing site, and fully comply with our quality procedures.

A marking of vehicles/vehicle components of the above mentioned type with different factory or trade marks but the same approval mark is only permissible if written consent has been obtained from the Vehicle Certification Agency.



Susan Owens Q.B.T.

01/08/07 VCA J	b No VSH180956
----------------	----------------

# **Friction test results**

Conducted in accordance with Annex 8, of ECE Regulation No. 90 Rev1 including supplement 2 to the 01 series of amendments. (TRANS/SC1/WP29/GRRF/R90 Rev 1).

Type of assembly:	Part Number DP11094 in material LE TD3 GG
	(Previously agreed single test reference)

Type of test:	Constant torque (para. 2.2.2.2)
μ <sub>op</sub> : 1	0.354
μ <sub>op:2</sub>	0.361
$\mu_{min}$ :	0.278
$\mu_{max}$ :	0.422

Test dates: 02/06/2006

Jusan Queus

Susan Owens Q.B.T.



01/08/07	VCA Job No	VSH180956
----------	------------	-----------

## **Bench tests**

Manufacturer:			
Type of brake lining assy:	DP11094 LE TD3 GG	Page	1/2

1. Shear strength test<sup>1</sup> (5.3.2.1 of ECE Regulation No. 90 Rev 1)

Sample	
Type of assembly:	DP11094 LE TD3 GG
Shear area [cm <sup>2</sup> ]:	43.46

<ul> <li>Shear strength measured</li> </ul>	
Mean value [N/cm²]:	630
Required [N/cm <sup>2</sup> ]:	250

Test date: 03/06/2006

1) Test procedure according to ISO Standard 6312 (2001)

Jusan Rivens

Susan Owens Q.B.T.



01/08/07	VCA Job No	VSH180956
	1	
Manufacturer:		
Type of brake lining assy:	DP11094 LE TD3 GG	Page 2/2

2. Compressibility test<sup>2</sup> (5.3.2.2 of ECE Regulation No. 90 Rev 1)

• Sample

Туре:	III		
Type of assembly: GG	DP11094	LE	TD3
Thickness, $d_0$ (nominal value) [mm]:	18.5		
Pad area [cm <sup>2</sup> ]:	43.464		
Ram dia (corresponding to caliper piston dia) [mm]:	54		

• Compressibility at specific surface pressure of 8000 kPa

Measured at ambient temperature

Mean value:  $\frac{d_4 - d'_3}{d_0} = 0.16$  % Required:  $\leq 2\%$ 

Measured at 400°C

Mean value:  $\frac{d_4 - d'_3}{d_0} = 0.65\%$ Required:  $\leq$  5%

### Test dates: 03/06/2006

2) Test procedure according to ISO Standard 6310 (2001)

Jusan Owens

Susan Owens Q.B.T.



												Max Th
											C	Disc / Disc /
										OE Caliper	S/V C	0rum / Shoe
MAKE		MODEL 1	MODEL 2	MODEL 3	MODEL 4	MODEL 5	F/R	D A	ΤE	Manufacturer	Dr D	Dia Width
L0381	FORD	Transit 2006>	260	FWD			F	04 06		Bosch	V	
L0381	FORD	Transit 2006>	280	FWD			F	04 06		Bosch	V	
L0381	FORD	Transit 2006>	300	FWD			F	04 06		Bosch	V	



		VEHICLE /											
	BRAKING	CALIPER	PAD			MAX	80% V	AXLE	VEHICLE	ENERGY	MAXIMUM		VEHICLE
CALIPER	SPLIT F/R,	PISTON	FRICTION	HERST	TYP / SCHL	SPEED	MAX	WEIGHT	WEIGHT	FACTOR	ROLLING	INERTIA	INERTIA
ACTUATION	DIAG or H / I	DIA	AREA mm^	NUMBER	NUMBER	Km/h	Km/h	UN-LADEN	LADEN	.5 MV 2	RADIUS	UNLADEN	LADEN
Hyd	F/R					150	120		2450	17640000	0.33	0	102.719925
Hyd	F/R					150	120		2710	19512000	0.33	0	113.620815
Hyd	F/R					150	120		3000	21600000	0.33	0	125.7795





